

IDO-GU1 Intelligent USB Speakerphone



Microphone

The Speakerphone is equipped with full duplex omni-directional microphone provides wideband audio, and built in powerful speaker covering a distance of up to 10 feet in all directions.



Speaker

The IDO-GU1 features in advanced Digital Signal Processing of echo cancellation and Noise suppression technology to ensure excellent audio clarity on both ends of the line, It also comes with a 3.5mm headset port that allows the user to switch from a conference call to a private conversation.

Compatible with Most popular Web Conferencing software

All these features make it the perfect solution for spontaneous conferencing and collaboration which is compatible with various telecommunication platforms including WebEx, Lync, Skype for Business, BlueJeans, Zoom, and Jabber for easy integration into your existing videoconferencing infrastructure.

Features:

- 3M diameter Pick up Range
- USB cable
- Full duplex performance
- LEDS for speakerphone streaming, mute, hold andBattery-life indication
- Mini USB for battery charge
- Touch controls for volume down, up, mute,
 Power on/Off, Mic select

Microphone:

- 360° omni-directional
- Frequency response: 20 Hz-15kHz
- Sensitivity: -22 DBFS

Speaker:

- Echo cancellation
- Noise suppression

Web: www.ipidio.com email: info@ipidio.com



IDO-GU1 Intelligent USB Speakerphone



specification sheet

Model No.		IDO-GU1
Microphone	type	Full duplex OMNI-Directional microphone
	Sensitivity	-22dBFS
	S/N Ratio	60dB
	Frequency range	20Hz-15kHz
Speaker		Built in powerful speaker, AGC provided excellent audio quality
Echo cancelation		Advanced echo cancellation up to 256ms
Noise suppression		>15dB
Sampling rate		16kHz/48kHz
Pick up diameter range		Max 3 meters, suggest to work in 2 meters diameter distance
Transmission mode		USB cable
Audio output		3.5mm socket for headset, Amplifier
Battery Charge Socket		Mini USB
Control		Button Control
Button functions		Power on/Off, Mute, silent speaker, HiFi mode, Volume UP/Down
Status display		Double-color LED indicator light
Power		DC5V \pm 0.2V,1A
Work Temperature		0-50℃
Environment Humidity		0-95% RH
L X W X Hmm		178mmx 162mmx 47mm
Weight		350g

What's in package:

1x Speakerphone 1x manual book







Web: www.ipidio.com email: info@ipidio.com